

GE RING STRIPNAIL GAS & NAIL PACK 2,87X50MM CARBON STEEL STANDARD TENSILE

GE51AABKR-FC



APPLICATIONS

Framing, sheathing, subfloor, decking, trusses, pallets and crates


TECHNICAL SPECIFICATIONS

Collation angle	34 °
Collation type	Paper collated
Wire material	Carbon steel standard tensile
Finish	Regular galvanised
Coating	Sencoted
Nail head type	Clipped head
Head width	6.81 - 7.21 mm
Head length	4.85 - 5.2 mm
Nail shank type	Ring shank
Point type	Diamond
Pointangle	40 °
Nail length	50 mm
Nail diameter	2.87 mm

LOGISTICAL SPECIFICATIONS

GTIN	8718035000460
Package quantity	2000 pieces
Net weight	4.2 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

CE fastener type	Round cross-section ring shank nail
Protection level in micron	≤5
Service class	1
Coating type	Coating type 3
Coating length	28 mm
Head cross sectional area	30 mm
Threaded/profiled length	30 mm
Characteristic yield moment	2525 Nmm
Characteristic head pull through parameter	20.3 N/mm ²
Characteristic tensile strength	695 N/mm ²