WOOD TO WOOD SCREW PH2, 4,2X45MM CARBON STEEL STANDARD TENSILE

MAKE IT LAST.



42KS45MY

APPLICATIONS
Particle boards, subfloor


TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Flat
Screw recess	Phillips 2
Screw thread type	Coarse
Rotations per minute	2500 RPM
Wire material	Carbon steel standard tensile
Finish	Yellow zinc
Head diameter	8 mm
Point type	Type 17 cut point
Pointangle	23 °
Screw length	43.8 - 46.2 mm
Screw diameter	4.05 - 4.35 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274022611
Package quantity	1000 pieces

FASTENER SPECIFICATIONS



43.8 - 46.2 mm

4.05 - 4.35 mm

CE SPECIFICATIONS

Inner threaded diameter	3.05 mm
Threaded/profiled length	29 mm
Characteristic yield moment	3283 Nmm
Characteristic head pull through parameter	16 N/mm²
Characteristic tensile capacity	4700 N
Torsional ratio	≥1,5
Characteristic torsional resistance	1.28 Nm
Characteristic torsional strength	3.4 Nm