



MAKE IT LAST.

KYOCERA SENCO UK Ltd.  
630 Europa Boulevard  
Gemini Business Park  
Warrington WA5 7YH, United Kingdom  
Tel: +44 (0) 1925 445566  
info@kyocera-senco.co.uk  
www.kyocera-senco.co.uk



## DECLARATION OF PERFORMANCE BL26APBF (v0)

Name	Senco cn flat bb. dp. ring 2,5x70mm
Article number	BL26APBF
GTIN	8715274177106

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK
Intended use	Dowel-type fastener
Unique identification code	BL26APBF
DOP No	BL26APBF
Designated standard	EN 14592:2008+A1:2012
AVCP	3
NB	1686

Declared performances		
Essential characteristics for: BL26APBF		Performance
Characteristic yield moment	$M_{y,k}$	1620 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	9.1 N/mm <sup>2</sup>
Characteristic head pull through parameter	$f_{head,k}$	25.5 N/mm <sup>2</sup>
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Carbon steel, SC 1, EN 1995-1-1

$f_{ax,k}$  en  $f_{head,k}$  are tested at a characteristic timber density of 350 kg/m<sup>3</sup>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO UK Ltd by:

Place and date of issue: Warrington,

Lars Aa. Mortensen  
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Nail diameter	$d$	2.5 mm
Head cross sectional area	$d_h$	27 mm
Nail length	$L$	70 mm
Threaded/profiled length	$l_g$	52 mm
Length of point	$L_p$	3.9 mm
Coating length	$L_h$	52.5 mm
Coating type	Type	Coating type 3
Reaction to fire		A1