

SENCO CN CON. HDG DP SM PLAIN 3,1X19MM CARBON STEEL STANDARD TENSILE



HJ11ASAVR

APPLICATIONS

Asphalt shingles, fiber glass shingles, siding, vapor barriers


TECHNICAL SPECIFICATIONS

Collation angle	16 °
Wounding type	Conical
Collation type	Wire collated
Wire material	Carbon steel standard tensile
Finish	Hot-Dipped galvanised 3
Coating	Plain
Nail head type	Full round head
Nail shank type	Smooth shank
Point type	Diamond
Pointangle	40 °
First welding wire distance	14.2 - 15.5 mm
Second welding wire distance	33.5 - 34 mm
Nail length	20 mm
Nail diameter	3.1 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274054865
Package quantity	1800 pieces
Net weight	3.14 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

Dit veld moet nog verwijderd worden EN 14592:2008+A1:2012

CE fastener type	Round cross-section plain shank nail
Service class	3
Coating type	Coating type 3
Head cross sectional area	72 mm
Characteristic yield moment	3000 Nmm
Characteristic head pull through parameter	25.5 N/mm ²
Characteristic tensile strength	620 N/mm ²