

FRAMEPRO651, CH FRAMING NAILER



2G2121N

The FramePro651 pneumatic framing nailer drives nails ranging from 2.9 to 3.3mm in diameter and 50 to 90mm in length. Being part of the Pro Serie, this clipped head nailer provides all the important features at an affordable price. Its compact design makes it easy to handle and easy on the arm. The 34° short, in-line magazines provide excellent maneuverability and line of sight.

APPLICATIONS

Framing, subfloor, sheathing, decking, siding, fencing, pallets and crates

FEATURES

- Aggressive toenail safety
- Dry fire lockout
- 360° Adjustable Exhaust
- Rafter hook
- Selectable Trigger
- Comfort grip
- Tool-free depth-of-drive

TECHNICAL SPECIFICATIONS

Oil free	No
Collation type	Paper collated
Type of nail	CH stripnails
Includes case	Yes
Net weight	3.81 kg
Firing mode	Dual
Magazine capacity	70 pieces
Air inlet size	3/8" female
Air consumption at 60 shots/minute	311.5 l/m
Operating pressure	4.8 - 8.3 bar

IDENTIFICATION

Article number	2G2121N
GTIN	0741474125218

FASTENER SPECIFICATIONS











FASTENERS

NAME	FINISH	CODE
GC smooth stripnail 2,87x55mm	Bright basic standard tensile	GCxxAPBKR
HC smooth stripnail 3,1x75mm	Bright basic standard tensile	HCxxAPBKR
GC smooth stripnail 2,87x70mm	Regular galvanised	GCxxAABKR
HC smooth stripnail 3,1x75mm	Regular galvanised	HCxxAAB
HC smooth stripnail 3,1x90mm	Bright basic standard tensile	HCxxAPB

ACCESSORIES



CODE CODE **NAME** NAME Lubrication oil for pneumatic tools with moisture guard PC1295Air plug 320 compatible 3/8"NPT, male 4000110

MATCHING PRODUCTS



NAME CODE AFN0022 AC24016, low noise compressor



NAME CODE AC33024UK2, Oil-less 230V UK compressor AFN0004UK2

NAME	CODE
AC20224BL-EU, air compressor 230V	AFN0038EU
NAME	CODE

AFN0031 AC32024. low noise compressor