

HJ SMOOTH COILNAIL 3,1X32MM CARBON STEEL STANDARD TENSILE



HJ15ASAVR

APPLICATIONS

Asphalt shingles, fiber glass shingles, siding, vapor barriers


TECHNICAL SPECIFICATIONS

Collation angle	16 °
Wounding type	Conical
Collation type	Wire collated
Wire material	Carbon steel standard tensile
Finish	Hot-Dipped galvanised 3
Coating	Plain
Nail head type	Full round head
Head diameter	8.99 - 10.21 mm
Nail shank type	Smooth shank
Point type	Diamond
Pointangle	40 °
First welding wire distance	14.2 - 15.5 mm
Second welding wire distance	33.5 - 34 mm
Nail length	32 mm
Nail diameter	3.1 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274054896
Package quantity	1800 pieces
Net weight	4.55 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

Harmonized standard	EN 14592:2008+A1:2012
CE fastener type	Round cross-section plain shank nail
Protection level in micron	30
Service class	3
Coating type	Coating type 3
Head cross sectional area	72 mm
Characteristic yield moment	3193 Nmm
Characteristic withdrawal parameter parallel	3.9 N/mm ²
Characteristic head pull through parameter	36.5 N/mm ²
Characteristic tensile strength	621 N/mm ²