



Applications

Drywall (to wood or steel studs), Cement board, Underlayment, Sheathing to steel, Metal framing, Structural steel decking, Rigid foam insulation

Features & Benefits


- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- 5000 RPM high speed brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Variable speed trigger with lock and reverse

Duraspin Screwdriver

Technical specifications

Dimension (LxWxH)	372x86x243 mm
Net weight	2,48 kg
Sound pressure level (Lpa)	63,5 dB
Sound power level (Lwa)	74,5 dB
Vibration level	1,1 m/s ²
Magazine capacity	50 pieces
Battery type	Li-Ion
Battery voltage	18 V
Battery ampere rating	3 Ah
Battery power	54 W
Recharge time 80%	15 minutes
Recharge time 100%	45 minutes
Shots per charge	2500
Number of batteries in kit	2 pieces
Voltage (ac)	230 V
Frequency	50 Hz
Electrical plug type	Continental
Rotations per minute (RPM)	5000 RPM

Fastener specification



Description

DS525-18V, DuraSpin Screwdriver

Art. Nr.

10A2001N

EAN code

8715274245225