



MAKE IT LAST.

# SENCOPUS GL RING COILNAIL 2,8X47MM CARBON STEEL STANDARD TENSILE

## SPL-GL20ASBCR



### APPLICATIONS

Packaging, pallets and crates, underlayment

### TECHNICAL SPECIFICATIONS

|                 |                               |
|-----------------|-------------------------------|
| Collation angle | 16 °                          |
| Wounding type   | Flat                          |
| Collation type  | Plastic collated 16mm         |
| Wire material   | Carbon steel standard tensile |
| Finish          | Hot-Dipped galvanised 3       |
| Coating         | Sencoted                      |
| Nail head type  | Full round head               |
| Head diameter   | 6.5 mm                        |
| Nail shank type | Ring shank                    |
| Point type      | Diamond                       |
| Pointangle      | 40 °                          |
| Nail length     | 47 mm                         |
| Nail diameter   | 2.8 mm                        |

### LOGISTICAL SPECIFICATIONS

|                  |               |
|------------------|---------------|
| GTIN             | 8715274139869 |
| Package quantity | 1200 pieces   |

### CE SPECIFICATIONS

|                                            |                                     |
|--------------------------------------------|-------------------------------------|
| CE fastener type                           | Round cross-section ring shank nail |
| Coating type                               | Coating type 3                      |
| Threaded/profiled length                   | 39 mm                               |
| Characteristic yield moment                | 3235 Nmm                            |
| Characteristic head pull through parameter | 29.58 N/mm <sup>2</sup>             |
| Characteristic tensile capacity            | 4.19 N                              |