



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
Pascallaan 88
8218 NJ Lelystad, The Netherlands
Tel: +31 (0)320 29 55 75
info@kyocera-senco.eu
www.kyocera-senco.eu



DECLARATION OF PERFORMANCE SPL-G656EUBXR (v1)

| | |
|----------------|---|
| Name | SencoPlus G6 offset ring stripnail 2,8x70mm |
| Article number | SPL-G656EUBXR |
| GTIN | 8715274139661 |

| Intended use/uses and identification of the construction product | |
|--|--|
| Manufacturer | Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad |
| Intended use | Dowel-type fastener |
| Unique identification code | SPL-G656EUBXR |
| DOP No | SPL-G656EUBXR |
| Harmonized standard | EN 14592:2008+A1:2012 |
| AVCP | 3 |
| NB | 1015 |

| Declared performances | | |
|--|--------------|---|
| Essential characteristics for: SPL-G656EUBXR | | Performance |
| Characteristic yield moment | $M_{y,k}$ | 3906 Nmm |
| Characteristic withdrawal parameter | $f_{ax,k}$ | 3,53 N/mm ² |
| Characteristic head pull through parameter | $f_{head,k}$ | 33,5 N/mm ² |
| Characteristic tensile capacity | $f_{tens,k}$ | NPD |
| Durability against corrosion | | Stainless Steel A4 (CRC III), SC 1,2 & 3, EN 1995-1-1 |

$f_{ax,k}$ en $f_{head,k}$ are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 26-02-2026

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

| Additional information | | |
|---------------------------|-------|----------------|
| Nail diameter | d | 2,8 mm |
| Head diameter | d_h | 6,5 mm |
| Head cross sectional area | d_h | 30 mm |
| Nail length | L | 70 mm |
| Length of point | L_p | 3,7 mm |
| Coating type | Type | Coating type 3 |
| Reaction to fire | | A1 |