



MAKE IT LAST.

# SENCOPUS HE RING STRIPNAIL 3,1X75MM CARBON STEEL STANDARD TENSILE

## SPL-HE57ASBK



### APPLICATIONS

Framing, pallets and crates, subfloor,  
wood-to-wood applications

### TECHNICAL SPECIFICATIONS

|                 |                               |
|-----------------|-------------------------------|
| Collation angle | 34 °                          |
| Collation type  | Paper collated                |
| Wire material   | Carbon steel standard tensile |
| Finish          | Hot-Dipped galvanised 3       |
| Coating         | Sencoted                      |
| Head diameter   | 7 mm                          |
| Head length     | 5.25 - 5.4 mm                 |
| Nail shank type | Ring shank                    |
| Point type      | Diamond                       |
| Pointangle      | 40 °                          |
| Nail length     | 75 mm                         |
| Nail diameter   | 3.1 mm                        |

### LOGISTICAL SPECIFICATIONS

|                  |               |
|------------------|---------------|
| GTIN             | 8715274140155 |
| Package quantity | 3000 pieces   |

### CE SPECIFICATIONS

|                                            |                                     |
|--------------------------------------------|-------------------------------------|
| CE fastener type                           | Round cross-section ring shank nail |
| Coating type                               | Coating type 3                      |
| Characteristic yield moment                | 3887 Nmm                            |
| Characteristic head pull through parameter | 18.09 N/mm <sup>2</sup>             |
| Characteristic tensile capacity            | 4.3 N                               |